


Model 6298 Hitch-Lock™ Trailer Guard

MOUNTING INSTRUCTIONS

1. Position base plate (#1) with the short end toward the pintle hook or ball type hitch. For maximum security, it is recommended that base plate be welded to trailer tongue.
2. Base plate can also be mounted to trailer tongue with two $\frac{5}{16}$ " x 1" bolts (#2) and lock nuts (#3) furnished. Use base plate as template and drill two $\frac{5}{16}$ " holes as shown.
3. Cover guard (#4) and padlock guard (#5) fit over base plate post as shown. Hole in base plate post accepts padlock (not furnished).

NOTE:


The *Hitch-Lock Trailer Guard* is an anti-theft device solely and is not designed or intended to be a safety device when trailer is being towed. Always comply with state and federal towing regulations. The *Hitch-Lock Trailer Guard* is not recommended for trailers equipped with surge brakes.



SPECIAL APPLICATIONS/MODIFICATIONS


If your trailer is equipped with a mud guard, you may need to relocate the mud guard 2" - 4" further back on the trailer tongue to allow installation of the *Hitch-Lock* base plate (#1). See Figure 1.

Figure 1




If your trailer is an A-Frame model (similar to Figure 2), you may need to have a plate fabricated and installed to the underside of the frame to provide an attachment surface for the *Hitch-Lock* base plate (#1). See Figure 2.

Figure 2



If your trailer is designed with an open channel tongue, you will need to have a steel plate welded to the bottom of the tongue to provide an attachment surface for the *Hitch-Lock* base plate (#1). See Figure 3.

Figure 3



Model 6298 Hitch-Lock™ Trailer Guard Parts List

Ref. No.	Description	Qty. Req'd.	Part No.
1.	Base Plate	1	303294
2.	$\frac{5}{16}$ " UNC x 1" Flat Head Screw	2	205302
3.	$\frac{5}{16}$ " UNC Lock Nut	2	205077
4.	Cover Guard	1	403150
5.	Padlock Guard	1	403151

To order replacement parts: Call or fax 24 hours a day, seven days a week:

Parts Company of America

Tel: 1-800-323-0620; Fax: 1-800-PCA-FAX1

LIMITED THREE (3) YEAR WARRANTY

Dutton-Lainson Company provides the following three (3) year limited warranty to the original purchaser of D-L® ratchet winches, brake winches, worm gear winches, and tongue jacks;

Dutton-Lainson Company will, at its option, repair or replace free-of-charge any part or parts found to be defective in material or workmanship under normal use for the period of three (3) years from the original purchase date or, if that date cannot be established, the date of manufacture. This warranty is void if the product is not installed and used in accordance with the operating instructions, has been subject to alteration or damage, or is defective due to unauthorized service or repair. This warranty does not assure that the product shall remain useable for the three (3) year warranty period since the life of the product is dependent upon the manner and frequency of use.

Repair or replacement is the purchaser's sole remedy under this or any other warranty on the product, whether express or implied. **Dutton-Lainson Company shall not be liable for any incidental or consequential damages of any kind. Dutton-Lainson Company expressly disclaims any implied warranty of merchantability or fitness for particular purpose after the three (3) year warranty period.** Some states do not allow the exclusion of incidental or consequential damages or limitation of an implied warranty so the above exclusion and limitation may not apply to you.

To make a claim, contact Dutton-Lainson Company, Hastings, Nebraska 68902-0729, identify the product, and follow the instructions for return, which will be provided. Repair or replacement of the product, if found to be defective, will normally be completed within sixty (60) days after receipt. The purchaser will be responsible for shipping costs to the Company.

This warranty gives you specific legal rights, and you may have other rights which vary from state-to-state.



A DEPENDABLE COMPANY – SINCE 1886
DUTTON-LAINSON COMPANY
Hastings, Nebraska 68902-0729 • 402-462-4141 • FAX 402-462-2971

MADE IN
U.S.A.